

Unsupervised Steganalysis based on Artificial Training Sets

Daniel Lerch Hostalot
David Megías Jiménez

UOC Research Week 2016




STEGANOGRAPHY





+


```
00101011110  
00111011110  
01101001110  
11100101110  
00100101111  
00100101000
```




STEGANALYSIS


Information
Hidden?










TESTING SET








TESTING SET FROM DIFFERENT CAMERA


























Comparative analysis between supervised classification and ATS

| Test DB | LSB matching | | | | HUGO | | | |
|---------|--------------|-------------|----------|-------------|----------|-------------|-------------|-------------|
| | 0.25 bpp | | 0.10 bpp | | 0.40 bpp | | 0.20 bpp | |
| | SUP | ATS | SUP | ATS | SUP | ATS | SUP | ATS |
| BOSS | 0.96 | 0.98 | 0.90 | 0.94 | 0.78 | 0.87 | 0.67 | 0.79 |
| ESO | 0.37 | 0.94 | 0.50 | 0.98 | 0.50 | 0.83 | 0.45 | 0.86 |
| CALP | 0.51 | 0.96 | 0.57 | 0.94 | 0.48 | 0.90 | 0.48 | 0.84 |
| INTE | 0.47 | 0.98 | 0.50 | 0.98 | 0.51 | 0.95 | 0.51 | 0.95 |
| NRCS | 0.49 | 0.68 | 0.55 | 0.61 | 0.49 | 0.63 | 0.50 | 0.46 |
| ALBN | 0.57 | 0.99 | 0.65 | 0.98 | 0.50 | 0.97 | 0.50 | 0.91 |
| NOAA | 0.35 | 1.00 | 0.50 | 0.98 | 0.50 | 1.00 | 0.44 | 0.96 |

Conclusions:

- Tested with the algorithms LSBM, HUGO and WOW.
- Tested with the DBs: BOSS, ESO, CALP, INTE, NRCS, ALBN, NOAA.
- Tested with different cover/stego ratios.
- Avoids the Cover Source Mismatch problem
- More accurate than supervised classification.

Future work:

- Can ATS be applied to other fields?

Unsupervised Steganalysis based on Artificial Training Sets

Thank you for your attention

